

Product Description

CAPILENE® CE 80 B is a specialty polypropylene combining typical advantages of polypropylene random and heterophasic copolymers, and is designed for extrusion applications.

Features:	<ul style="list-style-type: none"> • Excellent impact • Very low stress whitening • Good organoleptic properties • Clarified 	<ul style="list-style-type: none"> • Excellent transparency • High gloss • Short cycle time
Uses:	<ul style="list-style-type: none"> • Detergent and cosmetics clear containers • High clarity films 	<ul style="list-style-type: none"> • Corrugated sheets • Profiles
Processing Methods:	<ul style="list-style-type: none"> • Blow Molding • Sheet extrusion 	<ul style="list-style-type: none"> • Thermoforming

Properties		Method	Typical Value*	Unit
Physical				
Melt Flow Rate	(230°C/2.16 kg)	ISO 1133	1.8	g/10 min
Mechanical				
Tensile Stress at Yield	(50 mm/min)	ISO 527-2	24	MPa
Tensile Strain at Yield	(50 mm/min)	ISO 527-2	21	%
Flexural Modulus	(5 mm/min)	ISO 178	850	MPa
Izod Impact Strength, notched	(+23°C)	ISO 180	55	kJ/m ²
Izod Impact Strength, notched	(-20°C)	ISO 180	4	kJ/m ²
Thermal				
Vicat Softening Temperature	(10 N)	ISO 306	131	°C
Heat Deflection Temperature	(0.45 MPa)	ISO 75-2	74	°C
Optical				
Haze	(1 mm plaque)	ASTM D1003	15	%

*Typical values; not to be construed as specifications.

Health, Quality, Regulations and Safety

This product is not classified as dangerous substance. Material safety data sheets, international standards certificates (e.g. ISO 9001) and other regulatory documents are available on our website. This product is not intended for use in medical or pharmaceutical applications and we do not support its use for such applications.